

SLUMP TEST SET

STANDARDS: EN 12350-2

The Slump test method is used for the determination of the consistency, the medium and high workability of fresh concrete.

Slump Test Set is supplied either galvanized or paint coated to prevent corrosion.

Stainless Steel Slump Test Set is also available.

The set consists of Slump Cone, Slump Cone Funnel, Slump Base Plate, Tamping Rod which is hemispherical at both ends, Rubber Mallet and Steel Ruler.

Round Scoop should be ordered separately.

Portable Slump Test Set is also available.

The Test consist of Slump Cone, Slump Cone Funnel, Slump Base Plate, Tamping Rod which is hemispherical at both ends, Rubber Mallet and Steel Ruler.

Base, manufactured from heavy duty galvanized steel, complete with clamps and measuring bridge which is also used as carrying handle.

The components of the set are fitted together for easy carrying. Very practical, robust, ideal for site use.

Technical Specifications:

Product Code	Product Name	Dimensions (cm)	Weight (kg)
HR-C0850	Slump Test Set	55x60x25	7,5
HR-C0860	Slump Test Set, Stainless Steel	55x60x25	8,5
HR-C0865	Portable Slump Test Set	55x60x25	10

Spare Parts & Accessories:

Product Code	Product Name	Dimensions (cm)	Weight (kg)
HR-C0850/1	Slump Cone	10x20x30	2
HR-C0850/2	Slump Cone Funnel	---	---
HR-C0850/3	Slump Base Plate	50x50x6	3
HR-G0763	Tamping Rod	Ø 1,6 x 60	0,950
HR-G0748	Rubber Mallet	---	---
HR-G0476	Steel Ruler	30	---
HR-G0621	Round Scoop, Medium	---	0,5



HR-C0850



HR-G0621



HR-C0865