

**ASPHALT MIXERS**

STANDARDS: EN 12697-35

This mixers has been designed to mix bituminous samples for compaction tests, Marshall and tensile splitting test and for other tests where uniformity is required.

Thanks to the planetary action this mixer ensures a complete and uniform mixing.

The machine is provided with a variable speed drive allowing to set a wide range of speeds.

A timer allows to select the mixing time or the continuous mixing.

The bituminous mix must be prepared at prescribed temperature for this reason the mixer can equipped with thermostatically controlled heater.

The mixer is supplied complete with suitable capacity bowl and the beater.

Electric heater should be ordered separately.



HR-AS1625



HR-AS1625/1

**Technical Specifications:**


Product Code	Product Name	Capacity (lt)	Dimensions (cm)	Weight (kg)	Power Supply
HR-AS1625	Asphalt Mixer	5	30x55x65	55	220 V, 50-60 Hz, 1 ph
HR-AS1630	Asphalt Mixer	10	70x75x80	75	220 V, 50-60 Hz, 1 ph
HR-AS1640	Asphalt Mixer	20	70x75x95	110	220 V, 50-60 Hz, 1 ph

**Spare Parts & Accessories:**

Product Code	Product Name	Capacity (lt)	Dimensions (cm)	Weight (kg)	Power Supply
HR-AS1625/1	Bowl for HR-AS1625	5	---	---	---
HR-AS1625/2	Beater for HR-AS1625	---	---	---	---
HR-AS1625/3	Electric Heater for HR-AS1625	---	Ø 25x30	5	220 V, 50-60 Hz, 1 ph
HR-AS1630/1	Bowl for HR-AS1630	10	---	---	---
HR-AS1630/2	Beater for HR-AS1630	---	---	---	---
HR-AS1630/3	Electric Heater for HR-AS1630	---	Ø 30x35	7	220 V, 50-60 Hz, 1 ph
HR-AS1640/1	Bowl for HR-AS1640	20	---	---	---
HR-AS1640/2	Beater for HR-AS1640	---	---	---	---
HR-AS1640/3	Electric Heater for HR-AS1640	---	Ø 40x40	10	220 V, 50-60 Hz, 1 ph



HR-AS1630



HR-AS1630/2



HR-AS1630/1



HR-AS1630/3